

# IBM System x3200



#### **Highlights**

- Affordable uni-processor tower server for medium-sized businesses or distributed large enterprises
- More availability and management features than other systems in its class
- Quad-core and dual-core Intel® Xeon® processors deliver high performance

The IBM System x3200 can help lower your IT costs throughout its business lifecycle. The x3200 is not only affordable to purchase, but it's also easy to manage and keep up to date.

#### Keep your business in business

With unprecedented system availability, the x3200 can help you maximize uptime for your file and print or network infrastructure applications. Select SATA, near-line SATA or Serial Attached SCSI hard disk drives (HDDs) depending on your reliability requirements. If a hard disk drive or power supply fails, the x3200 can stay up and running with redundant power supplies and hotswap SATA and SAS HDDs.

#### Protect your data, your investment

Standard on select models, integrated hardware RAID-0 or -1 provides protection for your business-critical data.

Optional upgrades to RAID-5 or tape backup solutions are also available.

### Manage your growth

The x3200 helps minimize management costs for distributed or remote applications. It supports industry-standard, IPMI-based systems management and the IBM Remote Supervisor Adapter II for advanced hardware management—enabling your IT staff to do more with less.

## Get it now

| IBM System x3200 at a glance                                |  |
|---|--|
| Form factor/height  | Tower/5U   |
| <b>Processor</b> (L2 cache/CPU GHz/ front-side bus MHz max) | Quad-Core Intel Xeon (2x4MB/2.13 GHz/1066 MHZ), Dual-Core Intel Xeon (4MB/up to 2.4 GHz/1066 MHz), Intel Pentium® D (dual-core) (2x2MB/up to 3.4 GHz/800 MHz) or Intel Pentium 4 (1MB/3.2 GHz/800 MHz) |
| Number of processors (std/max)                              | 1/1  |
| Memory¹ (max)   | Up to 8GB DDR II 667 MHz   |
| Expansion slots   | 3 PCI and 2 PCI-Express (x8, x1) Dedicated Remote Supervisor Adapter II slot Slotless hardware RAID-0, -1  |
| Disk bays (total/hot-swap)                                  | Four 3.5" simple-swap or hot-swap Serial ATA hard disk drives (HDDs) or four 2.5" or 3.5" hot-swap Serial Attached SCSI hard disk drives   |
| Maximum internal storage <sup>1,2</sup>                     | Up to 1.2TB Serial Attached SCSI (SAS) HDDs or up to 3.0TB Serial ATA HDDs   |
| Network interface   | Integrated Gigabit Ethernet  |
| Power supply (std/max)                                      | 400W 1/1 or 430W hot-swap redundant 2/2 (model dependent)  |
| Hot-swap components   | Hard disk drives, power supplies (model dependent)   |
| RAID support  | Integrated hardware RAID-0, -1 (model dependent) Optional upgrade to RAID-5 and RAID-6   |
| Ports   | Front: Two USB Rear: Four USB; one Ethernet; two serial; one parallel; keyboard and mouse  |
| Systems management  | IPMI 1.5-compliant mini-BMC, IBM Director, Alert Standard Format 2.0, IBM ServerGuide™, optional Remote Supervisor Adapter II and optional Remote Deployment Manager                                   |
| Operating systems supported                                 | Microsoft® Windows® Server™ 2003 Standard Edition/Enterprise Edition, Windows Small Business Server 2003, Red Hat Enterprise Linux®, SUSE Linux Enterprise Server, Novell NetWare, IBM OS 4690         |
| Limited warranty <sup>3</sup>                               | 1-year or 3-year onsite limited warranty (model dependent)   |

| For more information | ı                       |  |
|----------------------|-------------------------|--|
| World Wide Web       |                         |  |
| U.S.                 | ibm.com/systems/x       |  |
| Canada               | ibm.com/ca/en/systems/x |  |
| Buy Direct           |                         |  |
| U.S.                 | 1 888 SHOP IBM          |  |
| Canada               | 1 888 SHOP IBM          |  |
| Reseller locator and | generation information  |  |
| U.S.                 | 1 800 426-4968          |  |
| Canada               | 1 800 426-2255          |  |



© Copyright IBM Corporation 2007

February 2007 All Rights Reserved

This publication could include technical inaccuracies or photographic or typographical errors. This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. References herein to IBM products and services do not imply that IBM intends to make them available in other countries. Consult your local IBM business contact for information on the products or services available in your area.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

IBM, the IBM logo, ClusterProven, ServerGuide, ServerProven and System x are trademarks or registered trademarks of IBM Corporation in the United States, other countries or both. For a list of additional trademarks, visit **ibm.com**/legal/copytrade.shtml.

Intel, Pentium and Xeon are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Microsoft, Windows Server, and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.

- <sup>1</sup> Maximum internal hard disk and memory capacities may require the replacement of any standard hard drives and/or memory and the population of all hard disk bays and memory slots with the largest capacity supported drives available. When referring to variable speed CD-ROMs, CD-Rs, CD-RWs and DVDs, actual playback speed will vary and is often less than the maximum possible.
- <sup>2</sup> GB and TB = 1,000,000,000 and 1,000,000,000,000 bytes, respectively, when referring to storage capacity. Accessible capacity is less.
- <sup>3</sup> IBM hardware products are made from new parts, or new and serviceable used parts. Regardless, our warranty terms apply. For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services, including those designated as ServerProven® or ClusterProven®.

XSD02455-USEN-01